

TMA TRUCK MODELS

TMA1



TMA3



TMA4



METRO



| STANDARD FEATURES | TMA1 | TMA3 | TMA4 | METRO |
|--|------|------|------|-------|
| Minimum Standard Body Length | 15ft | 15ft | 18ft | 15ft |
| Minimum 7,500lb Host Vehicle | | | | X |
| TL-2 Plus (50 MPH) MASH-Approved Attenuator | | | | X |
| Scorpion II TL-3 (62.5 MPH) MASH-Approved Attenuator | X | X | X | |
| BLADE TL-3 (62.5 MPH) MASH-Approved Attenuator | X | X | X | |
| 33"W Buckets with Swing Gates & Adjustable Safety Hoop | | X | | |
| 60"W Buckets with Swing Gates & Adjustable Safety Hoop | | | X | |
| Steel TMA Body with Integrated Ballast Chambers | X | X | X | X |
| Non-Skid Coated Deck | X | X | X | X |
| Heavy-Duty Removable Racks | | X | X | X |
| 15-Lamp LED Solar Powered Arrow Board | X | X | X | X |
| 2 Back Up Cameras with 7" Monitor | X | X | X | X |
| LED Marker & Work Lights | X | X | X | X |
| LED Strobe Lights | X | X | X | X |
| Underbody Locking Toolbox | | | X | X |